NSN 5905-00-721-1450

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-721-1450 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.290 inches **Overall Height:** 0.325 inches **Overall Width:** 0.295 inches **Mounting Hole Diameter:** 0.091 inches **Shaft Diameter:** 0.140 inches **Shaft Length:** Between 0.020 inches and 0.060 inches **Body Length:** Between 1.230 inches and 1.270 inches **Body Width:** 0.295 inches **Body Height:** 0.325 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Fragility Factor:** Moderately delicate **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 5.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 200.0 single section

NSN 5905-00-721-1450

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Two unc 2-56 thd mtg screws and nuts

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0