NSN 5905-00-722-7744

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-722-7744

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.250 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-722-7744

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Standard Taper Curve Per Section
3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	A single section
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	3 tab, solder lug
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No

Fiig: A002a0