

View Online at <https://aerobasegroup.com/nsn/5905-00-723-4552>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.3750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.640 inches

**Undercut Diameter:**

0.550 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.550 inches

**Shaft Diameter:**

Between 0.0932 inches and 0.0935 inches

**Shaft Length:**

0.375 inches

**Body Length:**

1.140 inches

**Overall Diameter:**

0.550 inches

**Mounting Lip Diameter:**

0.5500 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

2.50 inch-ounces

**Maximum Running Torque:**

2.50 inch-ounces

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Function Conformity Tolerance Per Section:**

-0.05/+0.05 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0