Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-723-9094

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Overall Length:

0.485 inches

Terminal Length:

0.187 inches

Overall Height:

0.562 inches

Overall Width:

0.190 inches

Shaft Diameter:

0.093 inches

Shaft Length:

0.080 inches

Body Length:

0.405 inches

Body Width:

0.190 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

8280.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

8280.0



| Center To Center Distance Between Center Terminal And Outside Terminal: |
|---|
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0 to 50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.75 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |