## NSN 5905-00-723-9111

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-723-9111 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.248 inches and 2.290 inches **Body Diameter:** Between 0.859 inches and 0.891 inches **Shaft Diameter:** Between 0.2495 inches and 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.457 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.00850 inches **Shaft Runout:** 0.0005 inches **Pilot Diameter Runout:** 0.00300 inches **Shaft Radial Play:** 0.003 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi): 32.0

## NSN 5905-00-723-9111

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
24930-310063s1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0