NSN 5905-00-723-9199

Precision Wire Wound Variable Resistor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5905-00-723-9199 |
|---|
| Section Quantity: |
| 1 |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.375 inches |
| Mounting Bushing Length: |
| 0.312 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 20.000 kilohms single section |
| Function Conformity Tolerance Per Section: |
| -0.50/+0.50 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Function Characteristic Per Section: |
| Single section linear |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0