NSN 5905-00-723-9293

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-723-9293 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8180 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 2.000 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.007 inches **Shaft Diameter:** 0.2498 inches **Shaft Length:** 1.060 inches **Body Length:** 1.200 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0830 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:**

1.60 inch-ounces

Shaft Runout:
0.001 inches

Lateral Runout:
0.002 inches

Pilot Diameter Runout:
0.00100 inches

NSN 5905-00-723-9293

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
65.0 single section and 110.0 single section and 140.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
3 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
6 solder stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

No

NSN 5905-00-723-9293

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0