

View Online at <https://aerobasegroup.com/nsn/5905-00-724-3335>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.940 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.190 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.850 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

330.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, double throw, three positions maintained

Fragility Factor:

Moderately rugged

Undercut Length:

0.440 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

100.0 kilohms 2nd section

Rotary Actuator Travel In Angular Deg:

330.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 all sections

Switch Current Type And Rating In Amps:

3.000 ac/dc

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0