Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-724-5964

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** Between 0.525 inches and 0.545 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.182 inches and 0.197 inches **Mounting Hole Diameter:** Between 0.090 inches and 0.098 inches Shaft Diameter: Between 0.058 inches and 0.098 inches Shaft Length: Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.490 inches and 0.510 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Fragility Factor:** Moderately delicate Lateral Distance Between Mounting Hole Centers: Between 0.513 inches and 0.526 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft

NSN 5905-00-724-5964

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 100.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 7200.0 and 16200.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 wire lead **Specification Data:** 81349-mil-r-22097/3 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0