NSN 5905-00-725-6933

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-725-6933

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.150 inches
Body Length:
1.359 inches
Body Width:
0.313 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0 to 150.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-725-6933

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

100.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0