Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-725-7554

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.203 inches **Overall Width:** 0.443 inches Mounting Hole Diameter: Between 0.070 inches and 0.076 inches Shaft Diameter: Between 0.058 inches and 0.062 inches Shaft Length: 0.030 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.250 inches and 0.265 inches **Body Height:** Between 0.490 inches and 0.510 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 360.0 **Center To Center Distance Between Terminals:** 0.200 inches Lateral Distance Between Mounting Hole Centers: Between 0.515 inches and 0.530 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Left adjacent side single row **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0



Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0