NSN 5905-00-726-0158

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-726-0158 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established First Flat Length: 1.562 inches Flat Height: 0.344 inches **Body Diameter:** 12.000 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 2.000 inches **Body Length:** 3.000 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 335.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 20.0 **Mounting Facility Quantity:**

Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
1.000 ohms single section
Rotary Actuator Travel In Angular Deg:
335.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section

NSN 5905-00-726-0158

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1000.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No