

View Online at <https://aerobasegroup.com/nsn/5905-00-726-0491>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.3120 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.100 inches

**Undercut Diameter:**

1.312 inches

**Undercut Width:**

0.0930 inches

**Body Diameter:**

1.438 inches

**Shaft Diameter:**

Between 0.2494 inches and 0.2497 inches

**Shaft Length:**

0.625 inches

**Body Length:**

0.688 inches

**Mounting Lip Diameter:**

1.4380 inches

**Mounting Lip Depth:**

0.0730 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

349.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Maximum Running Torque:**

0.40 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

25.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.15/+0.15 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section absolute conformity

**Fixed Tap Quantity Per Section:**

2 single section

**Tap Location Tolerance Per Section:**

-2.0/+2.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

10000.0 single section and 15000.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0