NSN 5905-00-726-0557

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-726-0557

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.136 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.312 inches
Body Length:
1.448 inches
Overall Diameter:
1.047 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3605.0
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3605.0
Function Conformity Tolerance Per Section

-0.30/+0.30 single section

NSN 5905-00-726-0557

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-3.0/+3.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
Δ002a0	