Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-726-1699

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.094 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

#### Body Length:

## 0.562 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

1.000 kilohms single section

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0