Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-726-1701

Section	Quantity:

1

**Reliability Indicator:** 

Not established

## Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.375 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

5.000 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

#### Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5905-00-726-1701

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

**Fiig:** A002a0

