Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-726-1702

Section Quantity:

1

Reliability Indicator:

Not established

First Flat Length:

0.625 inches

Flat Height:

0.216 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Standard Taper Curve Per Section:

L single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0