## NSN 5905-00-726-9291

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-726-9291

-260.0/+260.0  Electrical Resistance: 0.250 ohms  Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
0.250 ohms  Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Body Diameter:
0.188 inches
Body Length:
0.500 inches
Power Dissipation Rating In Watts:
2.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmenta
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0