Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-728-4283

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

4.297 inches

Terminal Length:

0.555 inches

First Flat Length:

1.891 inches

Flat Height:

Between 0.339 inches and 0.349 inches

Body Diameter:

8.090 inches

Shaft Diameter:

Between 0.373 inches and 0.376 inches

Shaft Length:

Between 1.953 inches and 2.047 inches

Mounting Bushing Length:

0.375 inches

Body Length:

2.250 inches

Overall Diameter:

8.645 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Maximum Starting Torque:

160.00 inch-ounces

Maximum Stop Torque:

240.00 inch-ounces

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2



Terminal Location: Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 350.000 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 320.0 and 330.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 390.0 single section **Power Dissipation Rating Per Section In Watts:** 500.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-22/12 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0
