## NSN 5905-00-728-5162

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-728-5162 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.813 inches **Body Length:** 0.438 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Fragility Factor:** Rugged **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 250.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-00-728-5162

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity	<b>/</b> :
----------------------------	------------

1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0