NSN 5905-00-728-5167

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-728-5167 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.750 inches **Body Width:** 0.600 inches **Body Height:** 2.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Fragility Factor:** Moderately delicate **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 100.0 kilohms 4th section **Rotary Actuator Travel In Angular Deg:** 290.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air all sections **Resistance Tolerance Per Section In Percent:** -30.0 to 30.0 all sections **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 12 wire lead

N/a

Shelf Life:

NSN 5905-00-728-5167

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0