NSN 5905-00-728-5409

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-728-5409

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.220 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.969 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
200.000 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section

NSN 5905-00-728-5409

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power	Dissipation	Rating	Per	Section	ln	Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0