## NSN 5905-00-729-0564

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-0564

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.090 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.062 inches
Body Length:
1.328 inches
Body Width:
0.348 inches
Body Height:
0.406 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Fragility Factor:
Moderately delicate
<b>Lateral Distance Between Mounting Hole Centers:</b>
1.094 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
5.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:

3 wire lead

## NSN 5905-00-729-0564

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0