NSN 5905-00-729-0566

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-0566 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.505 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.375 inches **Screw Thread Diameter:** 0.060 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:**

Unf
Screw Thready Qty Per Inch (tpi):
80.0
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
500.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0

NSN 5905-00-729-0566

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 1 connector, receptacle Shelf Life: N/a **Unit Of Measure: Demilitarization:** No