NSN 5905-00-729-0567

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-0567 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 0.313 inches **Overall Height:** 0.375 inches **Overall Width:** 1.359 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.130 inches **Body Length:** 1.359 inches **Body Width:** 0.313 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 250.000 ohms single section **Rotary Actuator Travel In Angular Deg:**

9000.0

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-729-0567

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|--|
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0