

View Online at <https://aerobasegroup.com/nsn/5905-00-729-0568>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.312 inches

Terminal Length:

Between 0.172 inches and 0.204 inches

Overall Height:

Between 0.468 inches and 0.532 inches

Overall Width:

Between 0.234 inches and 0.266 inches

Mounting Hole Diameter:

Between 0.081 inches and 0.091 inches

Shaft Diameter:

Between 0.120 inches and 0.130 inches

Shaft Length:

Between 0.057 inches and 0.067 inches

Body Length:

Between 1.245 inches and 1.255 inches

Body Width:

Between 0.234 inches and 0.266 inches

Body Height:

0.312 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

Between 0.672 inches and 0.704 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Center To Center Distance Between Terminal Rows:

0.094 inches

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

200.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.312 inches and 0.344 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Clutch

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0