NSN 5905-00-729-0569

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-0569

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Height:
0.516 inches
Overall Width:
Between 0.276 inches and 0.286 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
0.062 inches
Body Length:
1.266 inches
Body Width:
0.266 inches
Body Height:
0.328 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
Between 0.672 inches and 0.702 inches
Fragility Factor:
Moderately delicate
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:

1.0 megohms single section

Electrical Resistance Per Section:

0.094 inches

NSN 5905-00-729-0569

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
7920.0
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0