Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-0569

view Online at https://defobasegioup.com/hsi/3303-00-723-0
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Height:
0.516 inches
Overall Width:
Between 0.276 inches and 0.286 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
0.062 inches
Body Length:
1.266 inches
Body Width:
0.266 inches
Body Height:
0.328 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
Between 0.672 inches and 0.702 inches
Fragility Factor:
Moderately delicate
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.094 inches
Electrical Resistance Per Section:
1.0 megohms single section

NSN 5905-00-729-0569

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 7920.0 **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A002a0

N/a

No