NSN 5905-00-729-0984

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-729-0984

Electrical Resistance: 1.500 kilohms Resistance Tolerance In Percent: 5.5000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avaid terminal each end Tests Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial calalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shell Life: Via Unit Of Measure: ————————————————————————————————————	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -5.000/4-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/-4350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Aktal terminal each end Test Data Document: 81349-mil+-28c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Unit Of Measure: — Demilitarization: No Filig:	-260.0/+260.0
Resistance Tolerance In Percent: 5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-55.0/ Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-25c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Na Unit Of Measure:	Electrical Resistance:
Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator:	1.500 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 25.0 25.0 25.0 25.0 25.0 25.0 25.0	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Rediability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: Bri349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Tests Data Document: B1349-milr-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: No Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+350.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mill-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	350.0
Inclosure Method: Uninclosed Terminal Type: Wire lead Rediability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mili-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Uninclosed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-55.0/+350.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Uninclosed
Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Terminal Type:
Note established Body Diameter: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Body Length: 0.188 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
D.188 inches Body Length: D.500 inches Power Dissipation Rating In Watts: D.500 inches Style Designator: Axial terminal each end Test Data Document: D.510 Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.510 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.510 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.511 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.512 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.512 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.513 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.513 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.514 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.515 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.515 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.515 Exercise Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; D.	Not established
Body Length: 0.500 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.188 inches
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.500 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.000 free air
Test Data Document: 81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-26c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
100100	A001a0