NSN 5905-00-729-1383

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-729-1383

Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
100.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Teminal Type: Wire lead Reliability Indicator: Not established
Not established
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
-55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established
Terminal Type: Wire lead Reliability Indicator: Not established
Wire lead Reliability Indicator: Not established
Reliability Indicator: Not established
Reliability Indicator: Not established Body Diameter:
Body Diameter:
0.156 inches
Body Length:
0.281 inches
Power Dissipation Rating In Watts:
0.125 free air
Special Features:
100 pct radiographic inspection x-ray with each item
Style Designator:
Axial terminal each end
Test Data Document:
94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, et
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0