## NSN 5905-00-729-7344

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-729-7344 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.375 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5905-00-729-7344

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0