## NSN 5905-00-731-1353

**Section Quantity:** 

Cylindrical w/readout Reliability Indicator:

**Body Style:** 

Not established Pilot Diameter:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-731-1353

Between 0.4020 inches and 0.4060 inches
Overall Length:
Between 1.454 inches and 1.610 inches
Body Diameter:
Between 0.734 inches and 0.766 inches
Mounting Bushing Length:
Between 0.328 inches and 0.360 inches
Body Length:
Between 0.969 inches and 1.031 inches
Overall Diameter:
Between 0.734 inches and 0.766 inches
Actuator Type:
Integral knob with counter
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3610.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
20.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
Between 0.275 inches and 0.285 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing

## NSN 5905-00-731-1353

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3620.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
$\label{thm:coefficient} \textbf{Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:}$
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: