NSN 5905-00-732-3878

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-732-3878

-500.0/+200.0 Electrical Resistance: 20.000 ohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Realiability indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mile-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Na Unit of Measure: Demilitarization: No Figis A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
20.000 ohms Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: N/a Unit Of Measure:	-500.0/+200.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+ 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.0125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Test Data Document: 81349-mill-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	20.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: N/a Unit Of Measure: - Demilitarization: No Fiig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -56.0/+166.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Tests Data Document: 81349-mili-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wrire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	165.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+165.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Not established
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	0.125 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
O.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-10509/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0