## NSN 5905-00-735-4668

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-735-4668

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Terminal Length:
0.375 inches
Body Diameter:
3.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
4.031 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.188 inches
Overall Diameter:
3.375 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
100.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
8.0 free air single section
Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 single section

## NSN 5905-00-735-4668

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Special Features:
Shaft is grooved at far end for retaining ring
Terminal Type And Quantity:
5 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0