

View Online at <https://aerobasegroup.com/nsn/5905-00-737-8560>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.5000 inches

Pilot Length:

0.0620 inches

Overall Length:

2.575 inches

Undercut Diameter:

0.962 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.1249 inches

Shaft Length:

0.620 inches

Body Length:

1.925 inches

Overall Diameter:

1.062 inches

Mounting Lip Diameter:

0.9688 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.75 inch-ounces

Maximum Running Torque:

0.75 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Rear end

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

30.000 percent, rated amperes c and better flooring

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

1800.0 single section

Rotary Actuator Travel In Angular Deg:

4320.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

10.0 7th secondary quality

Function Conformity Per Section:

Single section terminal base linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

7 oclock all primaries

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

4 binding post

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0