Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-738-2224

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.922 inches

Body Diameter:

1.812 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.781 inches

Mounting Bushing Length:

0.312 inches

Body Length:

1.141 inches

Overall Diameter:

2.156 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

1080.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

350.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.562 inches

Shaft End Play:

0.00500 inches

Shaft Runout:

0.0005 inches



Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.004 inches **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 100.000 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 1080.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section

Terminal Type And Quantity:

3 turret



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0