## NSN 5905-00-739-6695

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-739-6695 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.188 inches **Body Diameter:** 0.500 inches **Body Length:** 0.180 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 15.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method:** Printed circuit **Electrical Resistance Per Section:** 100.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.5 free air single section

## NSN 5905-00-739-6695

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Iva
Unit Of Measure:
Unit Of Measure: