NSN 5905-00-739-8033

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-739-8033

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -30.0/+30.0 Electrical Resistance: -4.000 kilohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -55.00 -55.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: -56.0/+350.0 Inclosure Method: -57.00
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Bedy Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document:
3.000 free air Style Designator: Axial terminal each end Test Data Document:
Style Designator: Axial terminal each end Test Data Document:
Axial terminal each end Test Data Document:
Test Data Document:
06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A001a0