NSN 5905-00-751-1290

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-751-1290 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Terminal Length:** 6.000 inches **Overall Height:** Between 0.290 inches and 0.310 inches **Overall Width:** Between 0.170 inches and 0.190 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.110 inches and 0.130 inches **Shaft Length:** 0.050 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.170 inches and 0.190 inches **Body Height:** Between 0.290 inches and 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

Electrical Resistance Per Section:

100.000 ohms single section

NSN 5905-00-751-1290

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0 to 70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: