Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-3277

Section Quantity:	
1	
body Style:	
Cylindrical bushing mounted	
Reliability Indicator:	
Not established	
Overall Length:	
Between 1.031 inches and 1.125 inches	
Body Diameter:	
Between 0.890 inches and 0.922 inches	
Shaft Diameter:	
0.249 inches	
Shaft Length:	
Mounting Bushing Length:	
0.500 inches	
Body Length:	
Between 0.437 inches and 0.469 inches	
Overall Diameter:	
1.274 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Starting Torque:	
6.00 inch-ounces	
Maximum Stop Torque:	
128.00 inch-ounces	
Nonturn Device Location:	
At 9 oclock	
Nonturn Device Radius:	
0.438 inches	
Fragility Factor:	
Moderately rugged	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Radially positioned over less than half the circumference	



**Mounting Method:** Locking bushing **Features Provided:** Shaft locking device **Electrical Resistance Per Section:** 1.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 251.0 and 318.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-94/4 government specification Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A002a0

N/a

---

No