Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-3377

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.344 inches **Body Diameter:** Between 0.484 inches and 0.516 inches Shaft Diameter: 0.125 inches Shaft Length: 0.625 inches Mounting Bushing Length: 0.500 inches **Body Length:** Between 0.437 inches and 0.469 inches **Overall Diameter:** Between 0.484 inches and 0.516 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 6.00 inch-ounces Maximum Stop Torque: 48.00 inch-ounces **Nonturn Device Location:** At 4 oclock and at 10 oclock **Nonturn Device Radius:** 0.245 inches **Fragility Factor:** Moderately rugged Screw Thread Diameter: 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Rear end



## **Mounting Method:** Locking bushing **Features Provided:** Shaft locking device **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 292.0 and 298.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** F single section **Test Data Document:** 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-94/3 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig:

A002a0

---

No