

View Online at <https://aerobasegroup.com/nsn/5905-00-752-3411>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0570 inches

Body Diameter:

Between 0.860 inches and 0.910 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.750 inches

Body Length:

Between 0.600 inches and 0.725 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.9050 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Terminal Location:

Rear end

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

2.000 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

90.0 single section and 270.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-600.0 to 600.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Fixed Tap Quantity Per Section:

2 single section

Tap Location Tolerance Per Section:

-1.0 to 1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0