

View Online at <https://aerobasegroup.com/nsn/5905-00-752-3919>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.200 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.086 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

325.0

Maximum Starting Torque:

0.05 inch-ounces

Maximum Running Torque:

0.05 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.063 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

750.0 ohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.30/+0.30 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 all sections

Terminal Type And Quantity:

3 solder stud and 3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0