NSN 5905-00-752-3995

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-3995

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.843 inches
Body Diameter:
Between 1.031 inches and 1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.312 inches
Overall Diameter:
1.515 inches
Undercut Diameter:
0.125 inches
Shaft Style:
Round, stepped
Shaft Bearing Type:
Ball
Actuator Type:
Dual concentric
Effective Electrical Rotation In Deg Angular Rotation:
292.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
194.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Mechanical Backlash In Deg Angular Rotation:

NSN 5905-00-752-3995

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fragility Factor:
Moderately rugged
Undercut Length:
0.375 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Cubic Measure:
1.377 cubic inches
Electrical Resistance Per Section:
500.0 kilohms 1st section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Resistance Tempurature Characteristic Range Per Section In Percent:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 all sections
120.0 all sections
120.0 all sections Power Dissipation Rating Per Section In Watts:
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent:
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature:
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section:
120.0 all sections Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity:
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life:
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Power Dissipation Rating Per Section In Watts: 2.0 free air 1st section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure:

A002a0