NSN 5905-00-752-6680

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-6680

Section Quantity:
1
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.138 inches
Shaft Diameter:
0.375 inches
Shaft Length:
1.000 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.000 kilohms single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
12.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section
-5.0/+5.0 single section
-5.0/+5.0 single section Function Characteristic Per Section:

NSN 5905-00-752-6680

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0