NSN 5905-00-752-6708

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-6708

Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
0.562 inches
Flat Height:
0.218 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.125 inches
Shaft Style:
Round, flatted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
250.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section

NSN 5905-00-752-6708

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Switch Current Type And Rating in Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0