NSN 5905-00-752-6738

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-6738 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.437 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.245 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Locking bushing Features Provided: Shaft locking device **Electrical Resistance Per Section:** 250.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-00-752-6738

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••					
וו	em	ш	112	riz	2tı	n	١.

No

Fiig:

A002a0