## NSN 5905-00-752-6744

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-6744

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-26.0/+26.0
Electrical Resistance:
18.000 kilohms
Resistance Tolerance In Percent:
-3.000/+3.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
7.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Height:
2.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
40.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.438 inches
Body Length:
1.062 inches
Body Width:
0.531 inches
Body Height:
0.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.719 inches
Power Dissipation Rating In Watts:
6.000 free air
Mounting Hole Size:

0.125 inches

## NSN 5905-00-752-6744

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Style	Desia	nator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

C	he	Ιf	ı	if	۸.
	rie			ш	μ.

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A001a0