## NSN 5905-00-752-6841

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-6841

Tompurature Coefficient Of Posistance In Dom Per Dog Coloius						
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0						
Electrical Resistance:						
10.000 ohms						
Resistance Tolerance In Percent:						
-1.000/+1.000						
Heat Sink Material:						
Aluminum alloy						
Heat Sink Length:						
12.000 inches						
Heat Sink Width:						
12.000 inches						
Heat Sink Thickness:						
0.125 inches						
Ambient Tempurature In Deg Celsius At Full Rated Power:						
25.0						
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:						
275.0						
Tempurature Range Of Tempurature Coefficient In Deg Celsius:						
-55.0/+275.0						
Inclosure Method:						
Encased						
Encased Terminal Type:						
Terminal Type:						
Terminal Type: Threaded stud						
Terminal Type: Threaded stud Terminal Length:						
Terminal Type: Threaded stud Terminal Length: 1.250 inches						
Terminal Type: Threaded stud Terminal Length: 1.250 inches Body Length:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches  Power Dissipation Rating In Watts:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches  Power Dissipation Rating In Watts: 100.000 free air						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches  Power Dissipation Rating In Watts: 100.000 free air  Mounting Hole Size:						
Terminal Type: Threaded stud  Terminal Length: 1.250 inches  Body Length: 4.500 inches  Body Width: 2.125 inches  Body Height: 2.188 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches  Power Dissipation Rating In Watts: 100.000 free air  Mounting Hole Size: 0.188 inches						

N/a

## NSN 5905-00-752-6841

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A001a0