NSN 5905-00-752-7042

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-7042 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.845 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 2.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.438 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 312.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:**

At 9 oclock **Nonturn Device Radius:** 0.531 inches **Mechanical Backlash In Deg Angular Rotation:** 1.5 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

NSN 5905-00-752-7042

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
_ocking bushing
Features Provided:
Shaft locking device
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
0.0 to 8.0 -55 degrees celsius single section and -0.0 to 4.0 -25 degrees celsius single section and -0.0 to 2.0 0 degrees celsius single
section and -0.0 to 0.0 25 degrees celsius single section and -3.0 to 3.0 85 degrees celsius single section and -0.0 to 6.0 120 degrees
celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0